

SPECIFICATIONS KIOSK

MODEL	HLBS INFOK	HLBS INFOK-TC
Type/Mounting	Free Standing	
Construction	Floor mounted with permanent base and screw less chassis The enclosure made of 1.6/2.0 mm thick CRCA steel sheet/Stainless steel sheet/polymer powder coated designed to work in harsh environmental Conditions and resistant.	
Display Type		
Type	Colour LCD Touch Monitor	
size	15"/17"/19"/21.5"/23" (inches)	
Resolution	1280x960/1280 x 1024 for 48.3 cm display	
Touch Screen	PCAP/CAPACITIVE/IR/SAW type with 3 mm antiglare & overlay tempered vandal resistant glass.	
LCD Touch Panel	Minimum 250 CD/m2 (NITS) brightness	
System Details		
Processor	4th/5th/6th Gen Intel Pentium/Core i3/i5/i7 - AMD A6/A8/A10-Intel Celeron/ Dual Core, 1/3/4/6/8 MB Cache.	Intel /AMD Processor 1 GHZ or Higher.
Chipset	Intel H/B/J Series/Q Series/AMD A6/A7/A8 Series	Intel / AMD Chipset
Memory	2/4 /8 GB 1600/1866/2133 MHz DDR3/DDR4 RAM	2 GB DDR3 RAM
ODD	8x/22x DVD ROM/RW Drive	Provision to connect external CD ROM
HDD/Storage	500Gb/1TB/2TB/3TB/4TB 5400/7200 rpm SATA III	4/8/16GB power IDE/SATA* flash
Expansion I/O	1 ps-2,4/6/8USB/1 Serial , LAN 10/100/GIGABIT	2PS-2, 4 USB, 1 Serial, LAN 10/100/VGA
Audio	1 x Line-out/1 Line-in	
Speaker	2x1.5 Watt, RMS Stereo speaker	
Operating System	Window 7/8.1/10 HE/SL/Pro	Windows 7/8 embedded (Pre loaded)
Cooling	1/2 Nos. Cooling fan	
Power Supply	180 - 240V, 50Hz, AC Supply/ External 45/65/120W Adapter	
Antivirus	Anti Virus with 60 Days/1 year license	
Environment		
EMC & Safety	FCC Class B for EMC and CE Marking or equivalent BIS/NABL CERTIFICATION for safety (for CPU and Display)	
Operating ambient	5 Deg.C to 40 Deg.C temperature	
Storage Temperature	(-)10 Deg.C to 55 Deg.C	
Operating Humidity	40 deg at 95% RH non-condensing	
Storage Humidity	40 deg 95% RH non-condensing	
Max. Power Consumption	120 Watts/200 Watts as per Requirement	80 watts
Overall Dimension	Height:180.34cm(71Inch),Width: 60cm(24 Inch),Depth:35cm(14 Inch)	
ADD ON ITEMS FOR KIOSK		
Thermal Printer	Thermal Printer, paper width 80 mm paper with Auto Cutter	
Keyboard	USB Interface/ PS-2 Interface, keyboard 64 keys with metallic track ball - IP-65 compliance,	



Certification

Approve by ETDC for Environment and Performance
 IS:9000/Part-2/Sec-4/1977(Reaffirmed in 2007)
 IS:9000/Part-3/Sec-5/1977(Reaffirmed in 2007)
 IS:9000/Part-5/Sec-1/1977(Reaffirmed in 2007)
 ISO 9001:2008, ISO 14001, CE

*Specifications are subject to change without notice. Images Displayed may vary from the original product.