



## HLBS HiNUM-T32 MULTIMEDIA PROJECTOR TECHNICAL SPECIFICATIONS

<b>Technology</b>	<b>DLP</b>
<b>Resolution</b>	1280X800
<b>Projection Method</b>	Front And Rear Both
<b>Projection Lamp</b>	UHP
<b>Brightness</b>	4500 ANSI Lumens
<b>Contrast Ratio</b>	22000:1
<b>Aspect Ratio</b>	16:9
<b>Zoom</b>	1.1
<b>Video Compatibility</b>	NTSE
<b>Computer Compatibility</b>	VGA To UXGA
<b>Lamp Life</b>	6000 HRS
<b>Lamp Hour Counter</b>	Built In
<b>Keystone Correction</b>	Vertical:±40°
<b>Speaker</b>	10 Watt
<b>Remote Control</b>	Full Function Remote Control
<b>I/O Ports</b>	HDMI In, VGA In, Audio In, VGA out , Audio Out, USB, RS232, LAN
<b>Throw Ratio</b>	<0.50
<b>Noise Level</b>	1 dB (Sleep Mode) :28 dB(Normal Mode)
<b>Operating Temperature</b>	0 deg. To 40 deg. Celsius
<b>Operating Humidity</b>	10-90% RH (Non Condensing )
<b>Power Supply</b>	210-240 V AC, 50/60 HZ
<b>Power Consumption</b>	265 W (Normal Mode ) : 0.5 W (Sleep Mode)
<b>Accessories</b>	Power Cable , VGA Cable , Remote Control, User Manual, Short Throw Arm 2*2 Feet