

HiNUM[®] Electronic Lectern


YOUR ONE-STOP MULTIMEDIA
EDUCATIONAL HUB



Gooseneck Mic



Laptop



Visual Presenter



Notebook Interface
Panel

MODEL: H44D-M

Upgrade your style
with the **EXCELLENCE**
of **TECHNOLOGY.**

Lectern Features

Used in University, Middle / High Schools, Meeting Room, Auditorium, Polytechnic High Tech Rooms, Smart Classroom.

- Ergonomically designed interface, expert quality, powder coated steel body.
- Easy moving wheels / caster with locks.
- The effective lesson through wire / wireless microphones (optional).
- High quality gooseneck microphone (low howling noise) (optional).
- Control all multimedia devices in classroom by the convenient integrated controller (optional).
- The super structure composite with 19" / 21.5" LED tablet monitor.
- Pneumatic lifting tablet monitor.
- Touch pen (optional).
- Movable keyboard tray with locks.
- Central control panel for switching all inputs (optional).
- Storage drawer for visualizer.
- Laptop interface / ports (optional).
- CD / DVD Drive (optional) (main frame in the cabinet).
- High Power Amplifier and speakers (optional).
- Central Locking – RFID / Bio Metric access (optional) for secure access to the system.
- 120mm sized cooling fan for device temperature control.
- International Standard equipment rack.
- Annotation software, white board, Screen Capturing Session recording and export to PDF.
- Podium Dimension- Front Height 44" / Height from Presenter side 42"/Top depth 28"/Top width of 26"



SPECIFICATIONS

Model	Hinum H44D-M SERIES	
Type/Mounting	Free Standing	
Construction	The Lectern is wheel mounting capable of moving in all direction with facility of locks. The Enclosure made of 1.6 mm thick CRCA polymer powder coated, design to work in harsh environmental conditions and vandal resistant	
Touch Display	19 Inches Digital Pen Display Graphics Tablets for Drawing wide LCD screen with 16:10 aspect ratio, 1440 x 900 pixels, 250 cd/m2, displays 17 millions colors with high 1000:1 contrast. 2048 pressure levels	21.5" Touch projected Capacitive p-cap Colour LCD Touch monitor, Antiglare Resolution 1280 X 1024/1920 X 1080 Brightness 250 nits
	Active Matrix Color TFT Scratch resistant when used with Electronic Pen / Stylus Built in highly sensitive interactive panel with TILT functionality	
Electronic Pen	Electronic pen with 2 buttons for better editing	Active Touch pen
Enclosure Ports	USB 3.0*2, VGA IN / HDMI IN / DVI ports, Power socket	
SYSTEM DETAILS		
Processor & Chipset	Support CPU (4th / 6th / 7th) Intel Pentium Dual Core / Quad Core - I3 / I5 / I7 AMD C70 / A8 / A10 Intel H / B / Q Series – AMD A Series	
Storage	32GB SSD/500GB / 1TB / 2TB 5400 rpm / 7200 rpm SATA III HDD	
Optical Drive	Support 1 x 8x/22x" ODD (Internal/External)	Support 1 x 8x / 22x" External ODD
Memory	RAM: 2/4/8/16 GB 1600/1866/2133/2400 Mhz DDR3 / DDR4	
LAN	10/100/1000 Mbps / wifi 802.11	
I/O Ports	6 3.0/3.1 USB Ports, DVI-D / VGA / 1*HDMI/2*DISPLAY pORT. Audio Ports for Mic and Headphone, PS/2 Keyboard / Mouse, RJ45 Port	
Speakers	2 x 25 Watt RMS Stereo	
CPU Cabinet	Mini / SFF / Tower	AIO
Certificate	BIS / ROHS / NABL / ISO 9001 / ISO 14001 / ISO 27001/ Green PC	
Operating System	Windows 10 Home / 10 Pro / LINUX	
Power Supply	180 – 240 V, 50Hz, AC Supply	
Cooling	1 / 2 Fans	
Power Management	Screen Blanking, Setup Password, Power supply SMPS Surge protected	
Antivirus	Microsoft Essential preloaded / Quick Heal Pro	
Accessories	Power Cable, USB wired 104 Keys Bilingual / Standard / Mechanical Keyboard, USB wired Mouse	
ENVIRONMENTAL		
EMC & Safety	FCC Class B for EMC and CE Marking (for CPU and Display)	
Temp. & Humidity	Operating Ambient temperatures – 5o C to 40o C Storage Temperature – (-)10o C to 55o C Operating Humidity – 40o at 90% RH non-condensing Storage Humidity – 40o at 90% RH non-condensing	
Annotation Software	Includes features like draw, choose pens, annotate, erase, colour, shape, size, text, edit, font, stamp, move, capture picture, video, save, rotate, undo, image gallery, print, floating keyboard and background	
Console Panel Ports	1 X RGB Input (other than input of PC in the Lectern to facilitate extra PC/Laptop/Visualizer. USB Port from the panel to facilitate inputs directly from the pen drive/USB based Hard disk drive. RJ45 LAN port at the panel to connect network. Selection switches to toggle between various sources for the output on the projection screen.	
Built-in Device	On the panel with easy access and control consisting of <ul style="list-style-type: none"> • Gooseneck Microphone • Hand held Cordless Microphone • Cordless Collar Microphone • Headphone Microphone • Audio system with built in Amplifier (60w/100/120 Watt Volume Control), Two/Four External Speakers RMS 25 Watt each. • Audio Visual Switch with 4 input ports (RGB / HDMI / DVI / RCA) and 2 Output ports for selection of source. 	
PROVISION FOR ADDITIONAL DEVICE		
	<ul style="list-style-type: none"> • Sliding tray for LAPTOP / NOTEBOOK / TABLET • Sliding Shelf for Input device / visual presenter / books / documents • Space for Keyboard and Mouse 	
Security	Built-In optional RFID authentication system or Bio metric for secure access to system (Central Locking)	
Warranty	12 months	



Technologies for Tomorrow

ODM/OEM Supplier

TAIWAN

Toptech, 1F No. 9, Alloy 8,
Lane 423, King-Kuan Rd, Pei-ta,
District - Taipei 112 Taiwan R.O.C.

INDIA

Bhopal (MP): 24/2, D Sector,
J.K. Road, Ind. Area, Govindpura
New Delhi: B-64, Kalkaji

Toll Free No. 1800 2701 244

email: sales@hlbstechnology.com
Website : www.hlbstechnology.com
